

ELECTROTECHNICAL TESTING INSTITUTE

Pod Lisem 129

171 02 Praha 8 - Troja

Notified Testing laboratory No. 1014

No. of the Test Report: 701952-01/07

No. of pages: 4 No. of annexes/No. of an. pages: 0/0

Issued: 22. 6. 2017



TEST REPORT FOR REACTION TO FIRE

Name of product: Cables

Type of product: XMVK, XMVKas

XMVK 3x2,5 mm² E_{ca} Ratings:

XMVKas 3G2,5 mm² E_{ca}

Part number:

Manufacturer: SC Omnicable SRL, str. Principala 175B,

Ernei, Mures, Romania

Production site: same as manufacturer

SC Omnicable SRL, str. Principala 175B, Ordering firm:

Ernei, Mures, Romania

Number of tested samples: 2

8.6.2017 Samples submitted on:

EZÚ Location of testing:

20. 6. 2017 through 20. 6. 2017 **Tested from**

Other data:

The product was tested EN 60332-1-1:04+A1:15,

EN 60332-1-2:04+A1:15+A11:16 according to:

Compiled by: Bretislav Dušek



Approved by: Jan Tůma Testing laboratory technical manager

Test results stated in the test report apply only to the tested subject and unless specified otherwise in the test report, the tests were performed using the method and under the conditions determined in the test regulations, technical norm, instructions for use and information provided by the manufacturer on the tested subject and using accessories required by the manufacturer. Without written consent, this report must not be reproduced in any other way than as a whole.

When referring to services of EZÜ, s. p., as an accredited laboratory, the customer specified in this report must use the following formulation: "Tested by test laboratory no. 1056, accredited by CAI".

Phone: +420 266 104 111 Fax: +420 284 680 070 www.ezu.cz Type: XMVK, XMVKas Test report No.: 701952-01/07

Test	Prescribed			Observed
Test on complete cable				
XMVK 3x2,5 mm ²				
Test for vertical flame propagation EN 60332-1-2, article 5 EN 60332-1-2, article 6				
outer diameterflame application timenot damage area from		[mm] [s]	60	10,2 60
lower edge of the top support - damage area from lower	min.	[mm]	50	296
edge of the top support - flame spread H	max. ≤	[mm] [mm]	540 425	465 69

Test type: Classificiation of electric cables according to reaction to fire

Standard: EN 50575, EN 13501-6,

EN 60332-1-2, EN 60332-1-1

Test of vertical flame spread on a single cable

Cable type: XMVK 3x2,5 mm²
Cable producer: SC Omnicable SRL

date of test: 20. 6. 2017

Classification according to EN 13501-6:

<u>E_{ca}</u>







Course of the tests



After test

Test	Prescribed			Observed
Test on complete cable				
XMVKas 3G2,5 mm ²				
Test for vertical flame propagation EN 60332-1-2, article 5 EN 60332-1-2, article 6				
outer diameterflame application timenot damage area from		[mm] [s]	60	12,6 60
lower edge of the top support - damage area from lower	min.	[mm]	50	317
edge of the top support	max.	[mm]	540	467
- flame spread H	≤	[mm]	425	150

Test type: Classificiation of electric cables according to reaction to fire

Standard: EN 50575, EN 13501-6,

EN 60332-1-2, EN 60332-1-1

Test of vertical flame spread on a single cable

Cable type: XMVKas 3G2,5 mm²
Cable producer: SC Omnicable SRL

date of test: 20. 6. 2017

Classification according to EN 13501-6:

E_{ca}



Before test



Course of the tests



After test

Type: XMVK, XMVKas Test report No.: 701952-01/07

Measuring and testing equipment

Used	Prescribed	Observed
Х	Metter 100 cm	N 400013
X	Slide caliper	259
X	Table stopwatch	551705
Х	Test under fire conditions	20 780

If an uncertainty of measurement is given, the expanded a measurement uncertainty is the product of the standard measurement uncertainty and coverage factor k = 2, which corresponds to a coverage probability of approximately 95% in a normal distribution.

Laboratory conditions during the test were in accordance with specifications of the standards listed on the first page of this test report.

Compiled by: Břetislav Dušek